

# TAPE PRODUCTS TECHNICAL DATA

## **PERMANENT / REMOVABLE FOAM TAPE**

### **DESCRIPTION:**

A double coated permanent/removable cross-linked, close cell polyolefin foam on a differential silicone coated liner. The liner is a densified paper that affords an easy release from the product.

### **PHYSICAL CHARACTERISTICS:**

Thickness in Rolls: 1/32" , 1/16" , 1/8"

Thickness in Pieces: Up to 2" Thick

Rubber based adhesive both sides

### **TYPICAL TEST DATA:**

Holding Power 1 lb. Per 1 sq. in. of tape - indefinitely (adhesive failure)

### **APPLICATIONS:**

Made to remove cleanly from most surfaces. For P.O.P displays and signage. It has a high tack side for bonding to most surfaces including corrugated, plastic, wood, and metal together to another substrate were removable side is affixed to. The flexible foam carrier fills gaps, which allows irregular surfaces to be joined. Thicker foams can be used to create a 3D effect.

### **APPLICATION CONDITIONS:**

45 F - 100 F

Surface must be clean and dry

### **SERVICE CONDITIONS:**

-20 F - 150 F

### **STORAGE CONDITIONS:**

50% Humidity at 72 F

**SHELF LIFE:** 1-2 Years